



**BLACKBELT MKII**

 **VICTRIX**  
A R M A M E N T S



# BLACKBELT MKII DATA SHEET

## Caliber / Twist rate

.308 Match (1/11 – 30")  
.308 Match (1/10 – 32")  
.308 Match (1/9,5 -32")  
.308 Win. (1/11 – 30")  
.300 WSM (1/10 – 32")  
.300 WSM (1/9,5 – 32")  
6,5 Creedmoor (1/7,5 – 30")  
6,5 Creedmoor (1/8,5 – 30")  
6,5×47 Lapua (1/7,5 – 30")  
6,5×47 Lapua (1/8,5 – 30")  
6 XC (1/8 – 28")  
6 BR (1/8 – 28")

## Barrel length

See section Caliber

## Weight

5.93 kg (13.07 lb) no scope, barrel length 28"  
6.10 kg (13.44 lb) no scope, barrel length 30"  
6.31 kg (13.91 lb) no scope, barrel length 32"  
The weight may vary of +/- 100 gr (3.53 oz) depending on the origin of the raw material

## Dimension

Closed overall length: 1205 mm (47.44")  
Extended overall length: 1245 mm (49.01")  
With barrel length 28"  
Closed overall length: 1256 mm (49.44")  
Extended overall length: 1296 mm (51.02")  
With barrel length 30"

Closed overall length: 1307 mm (51.45")  
Extended overall length: 1347 mm (53.03")  
With barrel length 32"

## Base rifle

Lapped button rifled barrel in AISI 416R, muzzle at 1" with black anti-glare finish  
Stock made of special carbon fiber with differentiated fibers by type and structure, enhancing rigidity and reducing torsion during firing  
Rear slider inclined at 3 degrees in length to offer the shooter the best comfort  
Integrated rubber butt pad with horizontal and vertical button adjustments  
Carbon fiber adjustable cheek-piece  
Anima® system, stock with a monolithic bedding in light alloy  
20 MoA removable action rail in light alloy  
Anschutz-type rail in light alloy for mounting a bipod  
Single-shot action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge  
Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock), two side lugs arranged at an angle of 105-degree lift, equipped with grooves and an interchangeable lever in light alloy  
PVD finish on the action and on the bolt  
Victrix Sporting V Adjustable single stage trigger: standard setting approx. 60 gr (2.12 oz)  
Heavy-duty reinforced transport case  
User manual and welcome kit

## Stock colour

Visible carbon fiber

*In case of difference between the data sheet images and website, the information and the images submitted on website has the priority*

*Accessories not mentioned in the standard configuration are not included in the price of the rifle*

Visible carbon fiber



VICTRIX  
SPORTING