

TARGET V MKII

ENGINEERED TO STAND APART. BUILT TO TAKE COMMAND.

Here, evolution isn't a detail — it's a mindset. Target MKII was conceived with a single purpose: o blend aesthetics with control, precision with character, innovation with identity. Its functional geometry, advanced technical materials, and commanding presence embody an uncompromising vision — a mechanical masterpiece forged to push boundaries with relentless elegance.





Caliber

.308 Match (1/11 – 30") .308 Match (1/10 – 32") .308 Match (1/9,5 -32") .308 Win. (1/11 – 30") .300 WSM (1/10 – 32") .300 WSM (1/9,5 – 32") 6,5 Creedmoor (1/7,5 – 30") 6,5 Creedmoor (1/8,5 – 30") 6,5×47 Lapua (1/7,5 – 30") 6,5×47 Lapua (1/8,5 – 30") 6 XC (1/8 – 28") 6 BR (1/8 – 28")

Barrel length

See section Caliber

Weight

6.33 kg (13.96 lb) no scope, barrel length 28" 6.50 kg (14.33 lb) no scope, barrel length 30" 6.71 kg (14.79 lb) no scope, barrel length 32" The weight may vary of +/- 100 gr (3.53 oz) depending on the origin of the raw material

Dimension

Overall length 1205 mm (47.44") Extended overall length: 1245 mm (49.01") With barrel length 28"

Overall length 1256 mm (49.44") Extended overall length: 1296 mm (51.02") With barrel length 30"

Overall length 1307 mm (51.45") Extended overall length: 1347 mm (53.03") With barrel length 32"

Base rifle

Lapped button rifled barrel in AISI 416R, muzzle at 1"
Composite stock with monocoque carbon fiber components and special design to maximize structural rigidity and minimize unwanted flexing and twisting

Rear slider inclined at 3 degrees in length to offer the shooter the best comfort

Integrated rubber buttpad with horizontal and vertical button adjustments

Carbon fiber adjustable cheek-piece

Anima® system, stock with a monolithic bedding in light alloy 20 MoA removable action rail in light alloy

Anschutz-type rail in light alloy for mounting a bipod

Single-shot action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge

Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock), two side lugs arranged at an angle of 105 degree lift, equipped with grooves and an interchangeable lever in light alloy

PVD finish on the action and on the bolt

Victrix Sporting V Single-stage adjustable trigger: standard setting approx. 60 gr (2.12 oz)

Heavy-duty reinforced transport case
User manual and welcome kit

Stock colour

The stock is available in the color: Razor Grey

Optional

Mirage band with an innovative quick-mount system

In case of difference between the data sheet images and website, the information and the images submitted on website has the priority

Accessories not mentioned in the standard configuration are not included in the price of the rifle





