



# Lupus

## CALIBER / TWIST RATE

308 Win Match (1/10)  
6.5 Creedmoor (1/8.5)  
22 LR (1/16)

## BARREL LENGTH

16"

## WEIGHT

4,45 kg (9.81 lb) with a magazine and no scope (Centerfire)  
4,15 kg (9.15 lb) with a magazine and no scope (Rimfire)

## DIMENSION

Overall length (Centerfire): 935 mm (36.81")  
with barrel and muzzle brake

Overall length (Rimfire): 875 mm (34.45")  
with barrel and muzzle thread protector

## FINISH

Walnut

## CONFIGURATION

Match-grade button rifled barrel  
Fixed wooden buttstock with recoil buttpad  
Hybrid forend made of lightweight alloy and wood, featuring lower and lateral attachment interfaces for accessories  
Surface PVD finish on the action and on the bolt  
Transport case  
User manual and welcome kit

*Unless otherwise stated in writing, only configuration and equipment listed specifically listed are included; any accessory not explicitly mentioned is excluded.*

### Centerfire

10-round double-stack metal magazine  
Victrix ProAngle muzzle brake  
20 MoA removable action rail in light alloy  
Short action worked out from billet through milling and turning with finish on electro-discharge  
Bolt with three asymmetric lugs equipped with longitudinal grooves and an ergonomic interchangeable bolt lever  
Victrix Sporting Plus adjustable Single-stage trigger with a two-position safety: standard setting approx. 400 g (14.11 oz)

### Rimfire

10-round single-stack polymer magazine  
Muzzle thread protector  
Action worked out from billet with a 20 MoA removable rail in light alloy  
Bolt with two asymmetric rear lugs, with a quick disassembly system, a double extractor and an ergonomic interchangeable bolt lever  
Victrix Sporting Plus adjustable Single-stage trigger with a two-position safety: standard setting approx. 250 g (8.82 oz)



*In the event of any discrepancy between images and specifications, the technical specifications published on the official website shall prevail.*



# Lupus

Centerfire - RH



Centerfire - LH



Rimfire - RH



Rimfire - LH



*In the event of any discrepancy between images and specifications, the technical specifications published on the official website shall prevail.*