



Lynx

CALIBER / TWIST RATE

308 Win Match (1/11)
6.5 Creedmoor (1/8)
22 LR (1/16)

BARREL LENGTH

26" (Centerfire)
22" (Rimfire)

WEIGHT

6,00 kg (13.23 lb) with a magazine and no scope
(Centerfire)
6,15 kg (13.56 lb) with a magazine and no scope
(Rimfire)

DIMENSION

Overall length: 1235 mm (48.62")
with barrel length 26" and muzzle brake

Overall length: 1050 mm (41.34")
with barrel length 22" and muzzle thread protector

FINISH

Walnut

CONFIGURATION

Match-grade button rifled barrel
Buttstock with recoil buttpad and adjustable cheek rest; wooden slider
Hybrid forend made of lightweight alloy and wood, featuring a full-length integrated Arca rail on the underside and a lateral accessory mounting system
Surface PVD finish on the action and on the bolt
Transport case
User manual and welcome kit


Unless otherwise stated in writing, only configuration and equipment listed specifically listed are included; any accessory not explicitly mentioned is excluded.

Centerfire

10-round double-stack metal magazine
Victrix ProAngle muzzle brake
20 MoA removable action rail in light alloy
Short action worked out from billet through milling and turning with finish on electro-discharge
Bolt with three asymmetric lugs equipped with longitudinal grooves and an ergonomic interchangeable bolt lever
Victrix Sporting Plus adjustable Single-stage trigger with a two-position safety: standard setting approx. 400 g (14.11 oz)

Rimfire

10-round single-stack polymer magazine
Muzzle thread protector
Action worked out from billet with a 20 MoA removable rail in light alloy
Bolt with two asymmetric rear lugs, with a quick disassembly system, a double extractor and an ergonomic interchangeable bolt lever
Victrix Sporting Plus adjustable Single-stage trigger with a two-position safety: standard setting approx. 250 g (8.82 oz)



In the event of any discrepancy between images and specifications, the technical specifications published on the official website shall prevail.



Lynx

Centerfire - RH



Centerfire - LH



Rimfire - RH



Rimfire - LH



In the event of any discrepancy between images and specifications, the technical specifications published on the official website shall prevail.