



# Motion

## CALIBER / TWIST RATE

308 Win Match (1/11)  
 6.5 Creedmoor (1/8)  
 6.5 x 47 Lapua (1/8)  
 22 LR (1/16)

## BARREL LENGTH

26" (Centerfire)  
 22" (Rimfire)

## WEIGHT

7,10 kg (15.65 lb) with a magazine and no scope (Centerfire)  
 5,90 kg (13.01 lb) with a magazine and no scope (Rimfire)

## DIMENSION

Overall length: 1220 mm (48.03")  
 with muzzle brake and barrel length 26"

Overall length: 1055 mm (41.54")  
 with barrel length 22" and muzzle thread protector

## FINISH

Cobalt Strike

## CONFIGURATION

Buttstock with horizontal and vertical multi-adjustments via a rotary ring and an adjustable insulated cheek piece  
 High strength chassis in light alloy, ready for mounting a picatinny rail  
 Upgraded light-alloy forend with integrated Anschütz-type and ARCA rails, with a side quick-release system for fast accessory mounting  
 Ergonomic and interchangeable grip for standard AR flat top platform  
 PVD surface coating on action and bolt  
 Transport case  
 User manual and welcome kit


*Unless otherwise stated in writing, only configuration and equipment listed specifically listed are included; any accessory not explicitly mentioned is excluded.*

### Centerfire

Barrel in special steel with a Heavy contour  
 Single feed and double stack 10-round metal magazine  
 Victrix ProAngle muzzle brake  
 20 MoA integrated action rail  
 Short action worked out from billet through milling  
 Bolt with six symmetric lugs, equipped with an interchangeable bolt lever  
 Victrix Sporting adjustable Single-stage trigger with a two-position safety: standard setting approx. 700 g (24.69 oz)

### Rimfire

Barrel in special steel with a Heavy contour  
 10-round single-stack polymer magazine  
 Muzzle thread protector  
 Action worked out from billet with a 20 MoA removable rail in light alloy  
 Bolt with two asymmetric rear lugs, with a quick disassembly system, a double extractor and an ergonomic interchangeable bolt lever  
 Victrix Sporting Plus adjustable Single-stage trigger with a two-position safety: standard setting approx. 250 g (8.82 oz)



*In the event of any discrepancy between images and specifications, the technical specifications published on the official website shall prevail.*



# Motion

Centerfire - RH




Centerfire - LH



Rimfire - RH



Rimfire - LH



*In the event of any discrepancy between images and specifications, the technical specifications published on the official website shall prevail.*