



SENTINEL

CALIBER / TWIST RATE

308 Winchester (1/11)
 6.5 Creedmoor (1/8)
 6.5 x 47 Lapua (1/8)
 22 LR (1/16)

BARREL LENGTH

24" (Centerfire)
 22" (Rimfire)

WEIGHT

6,00 kg (13.23 lb) with a magazine and no scope (Centerfire)
 4,80 kg (10.58 lb) with a magazine and no scope (Rimfire)

DIMENSION

Closed overall length: 940 mm (37.01")
 Open overall length: 1190 mm (46.85")
 with muzzle brake and barrel length 24"

Closed overall length: 805 mm (31.69")
 Open overall length: 1055 mm (41.54")
 with barrel length 22" and muzzle thread protector

FINISH

Field Grey

CONFIGURATION

Buttstock with horizontal and vertical multi-adjustments via a rotary ring and an adjustable insulated cheek piece
 High strength chassis in light alloy, ready for mounting a picatinny rail
 Reversible EVO button folding system
 Octagonal elliptic forend with lateral attachment system, with an integrated monobloc top rail 20 MoA and an integrated monobloc lower rail according to STANAG 4694/Mil std 1913
 Ergonomic and interchangeable grip for standard AR flat top platform
 PVD surface coating on action and bolt
 Transport case
 User manual and welcome kit


Unless otherwise stated in writing, only configuration and equipment listed specifically listed are included; any accessory not explicitly mentioned is excluded.

Centerfire

Barrel in special steel
 Single feed and double stack 10-round metal magazine
 Victrix ProAngle muzzle brake
 20 MoA integrated action rail according to STANAG 4694/Mil std 1913
 Short action worked out from billet through milling
 Bolt with six symmetric lugs, equipped with an interchangeable bolt lever
 Victrix Sporting adjustable Single-stage trigger with a two-position safety: standard setting approx. 700 g (24.69 oz)

Rimfire

Barrel in special steel
 10-round single-stack polymer magazine
 Muzzle thread protector
 Action worked out from billet with a 20 MoA removable rail in light alloy
 Bolt with two asymmetric rear lugs, with a quick disassembly system, a double extractor and an ergonomic interchangeable bolt lever
 Victrix Sporting Plus adjustable Single-stage trigger with a two-position safety: standard setting approx. 250 g (8.82 oz)



In the event of any discrepancy between images and specifications, the technical specifications published on the official website shall prevail.



SENTINEL

Centerfire - RH




Centerfire - LH



Rimfire - RH



Rimfire - LH



In the event of any discrepancy between images and specifications, the technical specifications published on the official website shall prevail.